



Commercial dryer (front control) for on-premises laundry applications

CD10

Dependable & efficient

- Superior airflow
 - Advanced blower system produces airflow of 220 cu. Ft. per minute
 - Fast-drying results with advanced airflow pattern
 - Minimum dry time
- Large capacity
 - Large 7.0 ct. ft. cylinder
- Door opening of 2.06 sq. ft. for fast and easy loading and unloading
- Time savings
 - Large, easy-clean lint filter is located upfront

Control

- Micro-Display control (MDC)
 - Offering the most essential features and programming options, the Micro-Display Control (MDC) on IPSO commercial dryers is user-friendly and features an attractive, easy-to-read design
- Touch pad control
 - Offers touch pad selection and combines both temperature and cycle
- Sound and light indicators
 - Indicate cycle status and coin validation
- Activation options
 - Available with coin drop installed, card ready or coin ready models
- Manual Programming and Audit
 - Program and audit use via the control panel



CD10 electric

CD10 gas

Model	BDEBLBGS431AW01	BDGBLBGS301AW01
Drum		
Capacity	8,2 kg	8,2 kg
Cylinder volume	198 l	198 l
Motor		
Motor size	0,25 kW	0,25 kW
Cabinet		
Cylinder finish	Galvanized	Galvanized
Colours	White	White
Door type (solid/window)	Solid	Solid
Heating		
Heat sources	Electric	Gas
Heating element	4000 kW	N/A
Connection		
Gas inlet connection	-	9,5 mm
Gas consumption	-	26,38 MJ/hr
Exhaust outlet diameter	102 mm	102 mm
Exhaust airflow	85 litres/sec	85 litres/sec
Operation		
Cycles	4	4
Cycle indicator lights	Y	Y
Power		
Electrical requirements (Voltage/Hz/Phases)	20AMP/240/50/1	10AMP/240/50/1
Weight		
Net weight	66 kg	68 kg
Shipping weight	70 kg	73 kg
Dimensions		
Unit dimensions		
Height	1027 mm	1027 mm
Width	683 mm	683 mm
Depth	711 mm	711 mm
Packing dimensions		
Height	1156 mm	1156 mm
Width	737 mm	737 mm
Depth	832 mm	832 mm

*Heights may vary slightly depending on levelling adjustments.

A B C D E F G H I J K

OPL * 1027 1006* 392* 102* 391 683 114* 10 203 711 597

