



Commercial dryer (front control) for vended laundry applications

CD10C

Dependable & efficient

- Superior airflow
 - Advanced blower system produces airflow of 220 cu. Ft. per minute
 - Fast-drying results with advanced airflow pattern
 - Minimum dry time
- Large capacity
 - Large 7.0 ct. ft. cylinder
- Door opening of 2.06 sq. ft. for fast and easy loading and unloading
- Time savings
 - Large, easy-clean lint filter is located upfront

Control

- Micro-Display control (MDC)
 - Offering the most essential features and programming options, the Micro-Display Control (MDC) on IPSO commercial dryers is user friendly and features an attractive, easy-to-read design
- Coin countdown start
 - Displays vend price and countdown coin and cycle time
- Touch pad control
 - Offers touch pad selection and combines both temperature and cycle
- Sound and light indicators
 - Indicate cycle status and coin validation
- Activation options
 - Available with coin drop installed, card ready or coin ready models
- Manual programming and audit
 - Program and audit use via the control panel



CD10C electric

CD10C gas

Model	BDEBXAGS431AW01	BDGBXAGS301AW01
Drum		
Capacity	8,2 kg	8,2 kg
Cylinder volume	198 l	198 l
Motor		
Motor size	0,25 kW	0,25 kW
Cabinet		
Cylinder finish	Galvanized	Galvanized
Colours	White	White
Door type (solid/window)	Solid	Solid or Window
Heating		
Heat sources	Electric	Gas
Heating element	4000 kW	N/A
Connection		
Gas inlet connection	-	9,5 mm
Gas consumption	-	26,38 MJ/hr
Exhaust outlet diameter	102 mm	102 mm
Exhaust airflow	85 litres/sec	85 litres/sec
Operation		
Cycles	4	4
Cycle indicator lights	Y	Y
Power		
Electrical requirements (Voltage/Hz/Phases)	20AMP/240/50/1	10AMP/240/50/1
Weight		
Net weight	68 kg	70 kg
Shipping weight	73 kg	75 kg
Dimensions		
Unit dimensions		
Height	1126 mm	1126 mm
Width	683 mm	683 mm
Depth	711 mm	711 mm
Packing dimensions		
Height	1156 mm	1156 mm
Width	737 mm	737 mm
Depth	832 mm	832 mm

*Heights may vary slightly depending on levelling adjustments.

