



Commercial dryer (rear control) for on-premises laundry applications

CD9

Dependable & efficient

- Superior airflow
 - Advanced blower system produces airflow of 220 cu. Ft. per minute
 - Fast-drying results with advanced airflow pattern
 - Minimum dry time
- Large capacity
 - Large 7.0 ct. ft. cylinder
- Door opening of 2.06 sq. ft. for fast and easy loading and unloading
- Time savings
 - Large, easy-clean lint filter is located upfront

Control

- Push-To-Start control
 - The Push-To-Start Control on commercial IPSO dryers assures reliable performance and helps optimize efficiency. The control panel offers convenient features - including an energy-saving cycle with an electronic timer
- Push-To-Start button
 - Features simple, push-to-start activation with an "In Use" LED light
- Four dryer heat cycle selections
- Offers Normal, Perm Press, Delicate and No Heat options



CD9 electric

CD9 gas

Model	BDEMNRGS431AW01	BDGMNRGS301AW01
Drum		
Capacity	8,2 kg	8,2 kg
Cylinder volume	198 l	198 l
Motor		
Motor size	0,25 kW	0,25 kW
Cabinet		
Cylinder finish	Galvanized	Galvanized
Colours	White	White
Door type (solid/window)	Solid	Solid
Heating		
Heat sources	Electric	Gas
Heating element	4000 kW	N/A
Connection		
Gas inlet connection	-	9,5 mm
Gas consumption	-	26,38 MJ/hr
Exhaust outlet diameter	102 mm	102 mm
Exhaust airflow	85 litres/sec	85 litres/sec
Operation		
Cycles	4	4
Cycle indicator lights	Y	Y
Power		
Electrical requirements (Voltage/Hz/Phases)	20AMP/240/50/1	10AMP/240/50/1
Weight		
Net weight	59 kg	61 kg
Shipping weight	64 kg	66 kg
Dimensions		
Unit dimensions		
Height	1092 mm	1092 mm
Width	683 mm	683 mm
Depth	711 mm	711 mm
Packing dimensions		
Height	1156 mm	1156 mm
Width	737 mm	737 mm
Depth	832 mm	832 mm

*Heights may vary slightly depending on levelling adjustments.

